

SCNC

SKILLS CANADA NATIONAL COMPETITION

# OCMT

OLYMPIADES CANADIENNES DES MÉTIERS ET DES TECHNOLOGIES

ASSEMBLY / ASSEMBLAGE

# SHEET METAL WORK TÔLERIE

POST - SECONDARY / NIVEAUX POSTSECONDAIRE





# Chassis Assembly

- 1. The two halves of the chassis are to be formed and them solid welded at 2 corners.
- 2. The wheels are to be attached to the chassis with 4 ¼" rods then double nutted with acorn nuts on outside of axles.

# Fender Assembly

1. Form bends & flanges for fender pieces. Fender 1 attached to fender 2 with a solid weld.

# Chassis to Fender Assembly

1. The chassis is attached to the fender assembly with 6 evenly spaced tack welds per side (long side)

### **Boiler Tube Assembly**

1. Form parts B1- B4, B4 attaches to B1 with a 1/4" double seam. B1, B2, B3 attach to each other through elbow edges

### Cab section Assembly

- 1. Form all H sections
- 2. H1 attaches to the two H2 sections via double seams. H3 attaches 5 to the two H2 sections via double seams. H4 attaches to the rest of the cab assembly by 4 blind rivets through the ½" flange on the 2-H2 parts.
- 3. H5 attaches to the cab section by 10 blind rivets, 2 per side plus 4 on back platform through  $\frac{1}{2}$ " flanges.

## Final Assembly

- 1. Boiler tube section is attached to cab section via ½" dovetail seam.
- 2. Chassis/Fender section is attached to boiler tube section via evenly spaced blind Rivets (3 per side) and to the cab section by riveting through the ½" flange at the rear of the fender section into the cab section with 4 blind rivets (2 per side).