

STROKE TOP END MEASUREMENT

# **Outdoor Power and Recreation Equipment**

POST-SECONDARY



## Lab #4 2 Stroke Top End Measurement

Engine is from a 2002 Yamaha SXViper

Do not start this lab until told that the competition is ready to start.

If there is something you don't understand, you may ask for clarification from the person in charge.

#### Locate and Record the following:

Engine Type 2 or 4 Stroke	
Type of Induction	
Engine Displacement	
Torque Specs	
Cylinder Head Nut Torque Final	10ftlb
Cylinder Base Nut Torque Final	15ftlb
Spark Plug Torque	14ftlb

### Using the supplied tools and equipment:

- Remove the cylinder heads and cylinders
- Remove the pistons from the connecting rods
- Carefully remove the top piston rings
- Measure all of the components and calculate clearances to complete the following table
- Record all measurements, and clearances in METRIC and in the tables provided and include the unit of measure.
- Re-assemble the top end components torqueing all fasteners to **the spec above.** Have the Judge verify your torque settings.



## Enter all measurements in the table on this page. Show calculations when possible.

Part name	Measurement							
Piston Diameter	MAG							
	CEN							
	PTO							
Cylinder Bore Diameter		D1	D2	D3	D4	D5	D6	
	MAG							
	CEN							
	РТО							
Piston To Cylinder Clearance	MAG							
	CEN							
	PTO							
Top Ring End Gap	MAG							
	CEN							
	РТО							
Top Ring Groove Clearance	MAG							
	CEN							



	РТО
Cylinder Taper	MAG
	CEN
	РТО
Cylinder Out of Round	MAG
	CEN
	PTO



